

# Aerospace Europe Conference 2023

## Joint 10<sup>th</sup> EUCASS – 9<sup>th</sup> CEAS Conference

---

Abstract #XXX (to be filled by the organizers)

Preferred Topics: FLOWCON

Corresponding author: ARNOULT Thomas

e-mail of corresponding author: arnault.t@gmail.com

Type: Oral

Status of corresponding author: Regular

---

## Closed-loop control of an open-cavity flow with magnetically actuated microvalves

### Authors

Thomas ARNOULT<sup>1\*</sup>, Colin Leclercq<sup>2</sup>, Charles Poussot-Vassal<sup>3</sup>, Cécile Ghouila-Houri<sup>1</sup>, Aurélien Mazzamurro<sup>1</sup>, Alain Merlen<sup>1</sup>, Eric Garnier<sup>4</sup>, Denis Sipp<sup>2</sup>, Philippe Pernod<sup>1</sup>, Abdelkrim Talbi<sup>1</sup>

\* Corresponding author

<sup>1</sup> Univ. Lille, CNRS, Centrale Lille, Yncréa ISEN, Univ. Polytechnique Hauts-de-France, UMR 8520 IEMN, F-59000 Lille, France, [thomas.arnault@centralelille.fr](mailto:thomas.arnault@centralelille.fr), [cecile.ghouila@centralelille.fr](mailto:cecile.ghouila@centralelille.fr), [aurelien.mazzamurro@centralelille.fr](mailto:aurelien.mazzamurro@centralelille.fr), [alain.merlen@univ-lille.fr](mailto:alain.merlen@univ-lille.fr), [philippe.pernod@centralelille.fr](mailto:philippe.pernod@centralelille.fr), [abdelkrim.talbi@univ-lille.fr](mailto:abdelkrim.talbi@univ-lille.fr)

<sup>2</sup> DAAA, ONERA The French Aerospace Lab, Meudon, F-92190, France, [colin.leclercq@onera.fr](mailto:colin.leclercq@onera.fr), [denis.sipp@onera.fr](mailto:denis.sipp@onera.fr)

<sup>3</sup> DTIS ONERA - The French Aerospace Lab, F-31055 Toulouse, France, [Charles.Poussot-Vassal@onera.fr](mailto:Charles.Poussot-Vassal@onera.fr)

<sup>4</sup> Univ. Lille, CNRS, ONERA, Arts et Metiers Institute of Technology, Centrale Lille, UMR 9014, Laboratoire de Mécanique des fluides de Lille—Kampé de Fériet, F-59000 Lille, France, [eric.garnier@onera.fr](mailto:eric.garnier@onera.fr)

### Abstract

The open-cavity is a commonly studied geometry in flow control applications. Its dynamics has been studied since Roshko [1], Pereira [2] or Plumblee *et al* [3] and makes it a convenient test-bed to test new actuators or control approaches. The complex dynamics developing in an open-cavity flow has been described by Rossiter [4] and consists in a boundary layer developing upstream the cavity, separating at the upstream corner and forming the shear layer. This shear layer undergoes hydrodynamic instabilities over the cavity and impacts the downstream corner of the cavity, where acoustic waves are generated. They propagate upstream the cavity and excite the shear layer instabilities. This results in self-sustained oscillations in the flow, which can induce structural vibrations and noise radiation [5], therefore damping these oscillations is of interest.

We integrate a linear array of 15 MMMS (Micro-Magneto-Mechanical Systems) microvalves [6] to an open-cavity upstream edge to perform closed-loop flow control experiments. The microvalves can generate both quasi-steady and pulsed jets and have the advantage to be able to follow arbitrary command signals, which is a key for closed-loop flow control. To induce pulsed jets, which consist in a modulation of the outlet velocity around a mean value, a source of pressurized air has to be supplied to the actuators, alongside with an electrical source.

The closed-loop control strategy relies on several steps. Firstly, a transfer function is identified between the actuators command and the pressure sensors placed at the cavity downstream edge, where the open-cavity flow dynamics is the most amplified. Secondly, using a structured  $H_\infty$  loop-shaping synthesis, an optimized controller is derived based on the identified transfer function. Thirdly, the obtained controller is implemented in the Dspace MicroLabBox real time controller and the controller command signal is fed to the microvalves.

For a freestream velocity of 20 m/s, the open-cavity flow consists in a low frequency periodic flow regime characterized by a resonant frequency of 128.6 Hz. Closed-loop flow control experiments have been carried out for several microvalves driving pressures. Particularly, for a driving pressure of 140 mbar for the entire array of actuators (corresponding to a flow rate of 12 L/min), the open-cavity resonant frequency sound pressure level is reduced by 14 dB in closed-loop, compared to the unforced case. Further experiments show the controller robustness towards modification of the freestream velocity by  $\pm 5\%$  and investigate the required number of actuators to reach the same reduction in the flow resonant frequency amplitude.

As a conclusion, this study shows the straightforward use of the MMMS microvalves (with the ability to be driven with any type of signal, as required in closed-loop) in the closed-loop control of a periodic open-cavity flow and constitutes a first step towards the closed-loop control of more complex flows such as quasi-periodic open-cavity flows.

## References

- [1] A. Roshko, ‘Some measurements in a rectangular cutout’, National Advisory committee for aeronautics, Technical note 3488, 1955.
- [2] J. C. F. Pereira and J. M. M. Sousa, ‘Experimental and Numerical Investigation of Flow Oscillations in a Rectangular Cavity’, Journal of Fluids Engineering, vol. 117, no. 1, pp. 68–74, Mar. 1995
- [3] Plumblee, Gibson, and Lassiter, ‘A theoretical and experimental investigation of the acoustic response of cavities in an aerodynamic flow’, Marietta, Georgie, Technical report WADD-61-75.
- [4] J. E. Rossiter, ‘Wind tunnel experiments on the flow over rectangular cavities at subsonic and transonic speeds’, RAE Technical Report No. 64037, 1964.
- [5] L. N. Cattafesta, Q. Song, D. R. Williams, C. W. Rowley, and F. S. Alvi, ‘Active control of flow-induced cavity oscillations’, Progress in Aerospace Sciences, vol. 44, no. 7–8, pp. 479–502, Oct. 2008.
- [6] P. Pernod et al., « MEMS magneto-mechanical microvalves (MMMS) for aerodynamic active flow control », Journal of Magnetism and Magnetic Materials, vol. 322, no 9-12, p. 1642-1646, May 2010.

## Acknowledgments

This work was funded by the French National Research Agency (ANR) in the framework of the ANR ASTRID MATURATION “CAMELOTT-MATVAL” Project. It is supported by the regional platform CONTRAERO, the CPER ELSAT 2020 Project and the CPER RITMEA 2021-2027 Project. The Innovation Defense Agency (AID) has also financially sustained this work. The authors also thank RENATECH, the French national nanofabrication network, and FEDER.