

Aerospace Europe Conference 2023

Joint 10th EUCASS – 9th CEAS Conference

Abstract #XXX (to be filled by the organizers)

Preferred Topics: PROPHY, (3 maximum from the list of topics)

Corresponding author: ACHESON Chris

e-mail of corresponding author: chris.acheson@vuw.ac.nz

Type: Oral

Status of corresponding author: Student

For student corresponding author: student member of one of the following:
RAeS

Title

Integration and Testing of a High Temperature Superconductor Magnet with a Central Cathode Electrostatic Thruster

Authors

Chris R. ACHESON ^{1*}, Ryota Nakano ², Betina Pavri ³, Jakub Glowacki ⁴, Kiyoshi Kinefuchi ⁵

* Corresponding author

¹ PhD Candidate, Robinson Research Institute, Victoria University of Wellington, 5010 Lower Hutt, New Zealand, chris.acheson@vuw.ac.nz

² PhD Student, Department of Aerospace Engineering, Nagoya University, Nagoya, Japan, nakano.ryota.m4@s.mail.nagoya-u.ac.jp

³ Senior Principal Engineer, Robinson Research Institute, Victoria University of Wellington, 5010 Lower Hutt, New Zealand, betina.pavri@vuw.ac.nz

⁴ Engineer, Robinson Research Institute, Victoria University of Wellington, 5010 Lower Hutt, New Zealand, jakub.glowacki@vuw.ac.nz

⁵ Associate Professor, Department of Aerospace Engineering, Nagoya University, Nagoya, Japan, kiyoshi.kinefuchi@mae.nagoya-u.ac.jp

Abstract

High temperature superconductor (HTS) materials have long been perceived as futuristic solutions to many problems in space, including magnetic shielding from cosmic rays [1], energy storage and power delivery [2], and propulsion applications requiring very high magnetic fields [3]. Some types of electric propulsion devices show improved performance when operating in higher magnetic fields [4] [5], and superconductor magnets can create higher fields than any other technologies [6]. There have recently been advances in combining superconductor technologies with thrusters to improve performance [7] [8]. However, traditional superconductor systems are designed for laboratory rather than in-space conditions, and as a result the existing supporting technologies are typically of laboratory scale [7]. To date, there are no publicly available examples of a fully developed superconductor magnet system operating in space, let alone one operating as part of a plasma thruster. Furthermore, the ground testing of superconductor plasma thrusters has thus far relied upon laboratory scale subsystems, such as convective cooling systems with a cryogen such as helium or liquid nitrogen to prevent the superconductor overheating and quenching. Replacing these subsystems with space-ready alternatives is a key milestone on the path to in-space deployment. In this study, a high temperature superconductor magnet was integrated with a plasma thruster of the central-cathode electrostatic type. The thruster performance parameters such as thrust, specific impulse and efficiency were shown to improve at high fields. The magnet's thermal design was experimentally validated, with cryogenic conditions maintained at fields of over 1 Tesla. This magnet was not cooled using conventional convective methods: instead, it was conductively cooled using a single stage Stirling cycle cryocooler via a copper thermal bus. This allows the compact, lightweight cooling subsystem to operate at power on the scale of 100W and with room temperature heat rejection, which could be integrated with a spacecraft's radiator panels in the future. This empirical evidence shows that a spaceflight-capable superconductor

magnet device is thermally and energetically feasible. It also demonstrates the virtue in utilizing an HTS magnet system to supply a magnetic field to a plasma thruster.

References

- [1] V. Calvelli, R. Musenich, F. Tunesi, and R. Battiston, "A Novel Configuration for Superconducting Space Radiation Shields," *IEEE Trans. Appl. Supercond.*, vol. 27, no. 4, pp. 1–4, Jun. 2017, doi: [10.1109/TASC.2016.2642638](https://doi.org/10.1109/TASC.2016.2642638).
- [2] N. Bizon, "Hybrid power sources (HPSs) for space applications: Analysis of PEMFC/Battery/SMES HPS under unknown load containing pulses," *Renewable and Sustainable Energy Reviews*, vol. 105, pp. 14–37, May 2019, doi: [10.1016/j.rser.2019.01.044](https://doi.org/10.1016/j.rser.2019.01.044).
- [3] M. Collier-Wright *et al.*, "High-temperature superconductor-based power and propulsion system architectures as enablers for high power missions," *Acta Astronautica*, vol. 201, pp. 198–208, Dec. 2022, doi: [10.1016/j.actaastro.2022.08.035](https://doi.org/10.1016/j.actaastro.2022.08.035).
- [4] D. R. Lev and E. Y. Choueiri, "Scaling of Efficiency with Applied Magnetic Field in Magnetoplasma dynamic Thrusters," *Journal of Propulsion and Power*, vol. 28, no. 3, pp. 609–616, May 2012, doi: [10.2514/1.B34194](https://doi.org/10.2514/1.B34194).
- [5] A. Sasoh, K. Mizutani, and A. Iwakawa, "Electrostatic/magnetic ion acceleration through a slowly diverging magnetic nozzle between a ring anode and an on-axis hollow cathode," *AIP Adv.*, vol. 7, no. 6, p. 065204, Jun. 2017, doi: [10.1063/1.4985380](https://doi.org/10.1063/1.4985380).
- [6] H. W. Weijers *et al.*, "High Field Magnets With HTS Conductors," *IEEE Transactions on Applied Superconductivity*, vol. 20, no. 3, pp. 576–582, Jun. 2010, doi: [10.1109/TASC.2010.2043080](https://doi.org/10.1109/TASC.2010.2043080).
- [7] A. S. Voronov, A. A. Troitskiy, I. D. Egorov, S. V. Samoilenov, and A. P. Vavilov, "Magnetoplasma dynamic thruster with an applied field based on the second generation high-temperature superconductors," *J. Phys.: Conf. Ser.*, vol. 1686, p. 012023, Dec. 2020, doi: [10.1088/1742-6596/1686/1/012023](https://doi.org/10.1088/1742-6596/1686/1/012023).
- [8] J. Zheng *et al.*, "Integrated study on the comprehensive magnetic-field configuration performance in the 150 kW superconducting magnetoplasma dynamic thruster," *Sci Rep*, vol. 11, no. 1, Art. no. 20706, Oct. 2021, doi: [10.1038/s41598-021-00308-4](https://doi.org/10.1038/s41598-021-00308-4).