

Aerospace Europe Conference 2023

Joint 10th EUCASS – 9th CEAS Conference

Abstract #XXX (to be filled by the organizers)
Preferred Topics: PROPHY / NEWSPA
Corresponding author: LA LUNA Simone
e-mail of corresponding author: simone.laluna@polimi.it
Type: Oral / Poster (Oral)
Status of corresponding author: Regular / Student (Student)

Title

Nitrous Oxide Modelling: from Single Phase Incompressible to FML Mass Flow Rate Model

Authors

Simone LA LUNA ^{1*}, Davide Zuin ², Filippo Maggi ³ Luca Magni ⁴, Nicola Foletti ⁵

* Corresponding author

¹ Politecnico di Milano, Via La Masa 34, 20156 Milano, Italy simone.laluna@polimi.it

² Politecnico di Milano, Via La Masa 34, 20156 Milano, Italy davide.zuin@polimi.it

³ Politecnico di Milano, Via La Masa 34, 20156 Milano, Italy, filippo.maggi@polimi.it

⁴ Politecnico di Milano, Via La Masa 34, 20156 Milano, Italy luca7.magni@mail.polimi.it

⁵ Politecnico di Milano, Via La Masa 34, 20156 Milano, Italy, nicola.foletti@mail.polimi.it

Abstract

Hydrazine is the state-of-the-art for various space propulsion systems applications varying from launchers, upper stages and satellites. However, hydrazine as a monopropellant and MMH (Monomethylhydrazine) or UDMH (Unsymmetrical Dimethylhydrazine) bipropellants are toxic, carcinogenic, and mutagenic. Special precautions have to be taken during all ground and operational phases when hydrazines are used. The toxicity and reactivity of hydrazine family propellants led to a significant increase in the costs for fuelling a spacecraft.

In this framework new “green” propellant technologies have been developed and their use and interest are increased both in commercial and institutional organization. In the definition of these new propellants, the word “Green” has to be intended as related to acute toxicity, due to their hydrazine alternative’s purpose.

Among the family of “green” propellants, one promising candidate to replace hydrazine is Nitrous Oxide. Alongside its “green” characteristics, N₂O owns an interesting property: self-pressurization. This added value makes Nitrous Oxide an important case study for the space propulsion industry, where the miniaturization trend requires storability, simplicity, lightness, and reliability in terms of propulsion unit [1]. Indeed, most propellants currently used do not possess self-pressurization feature and hence, they need to be pressurized. This is accomplished by turbo pumps or by expulsion systems (blowdown or regulated), which of course add weight and complexity to the propulsion system [2].

The aims of this paper are two: first compare the nitrous oxide mass flow rate models present in the literature with FML model [3] and finally presented a new preliminary conceptual mass flow rate model.

References

- [1] A. E. Nosseir, A. Cervone, and A. Pasini. Review of state-of-the-art green monopropellants: For propulsion systems analysts and designers. *Aerospace*, 8(1):20, 2021.
- [2] J. S. Tyll and R. Herdy. The nitrous oxide-propane rocket engine. Technical report, MICRO CRAFT INC UNTSVILLE AL, 2001.
- [3] S. La Luna, et al. A Two-Phase Mass Flow Rate Model for Nitrous Oxide Based on Void Fraction. *Aerospace*, 2022, 9.12: 828.