

Aerospace Europe Conference 2023

Joint 10th EUCASS – 9th CEAS Conference

Abstract #XXX (to be filled by the organizers)

Preferred Topics: FDGNCAV, SUSTP, PROPHY

Corresponding author: DI PASQUALE Giuseppe

e-mail of corresponding author: giuseppe.dipasquale@ienai.space

Type: Oral

Status of corresponding author: Student (PhD)

For student corresponding author: student member of one of the following:

None

Title

Variable-Performance Electrospray Maneuvers Optimization

Authors

Giuseppe DI PASQUALE ^{1*}, David Villegas-Prados ², Manuel Sanjurjo-Rivo ³, Daniel Pérez Grande⁴

* Corresponding author

¹ IENAI SPACE, 28919 Leganés, Spain, giuseppe.dipasquale@ienai.space

² IENAI SPACE, 28919 Leganés, Spain, david.villegas@ienai.space

³ Universidad Carlos III de Madrid, 28919 Leganés, Spain, msanjurj@ing.uc3m.es

⁴ IENAI SPACE, 28919 Leganés, Spain, daniel.perez@ienai.space

Abstract

Electric propulsion is establishing itself as an advantageous alternative to chemical propulsion for space mobility, due to the propellant savings deriving from the high exhaust velocities attainable. Among the various existing technologies, a growing interest is building up around electrosprays because of their competitive performance in the low power range, where Hall thrusters or gridded ion engines suffer from efficiency loss and become unappealing. Among other qualities, such as high efficiency, the use of liquid propellants, and nearly instantaneous operations, externally wetted electrospray can operate in different regimes depending on the difference of potential set-point [1]. The ionic and droplet regime, which are characterized respectively by high specific impulse and high thrust-to-power ratio, could be combined by switching dynamically between them throughout the maneuver, improving the exploitation of the performance of the thruster. In principle, this enables trading thrust for specific impulse when most energetically convenient, and vice-versa. Additionally, the high thrust-to-power ratio mode could be exploited for collision avoidance maneuvers, improving the responsiveness of the satellite. This work presents the application of a methodology for optimizing variable-performance electrospray maneuvers [2], focusing on small satellites in LEO. The methodology relates the set-point selection of the thruster to a function describing the thrust effectivity [3] along the orbit. The parameters of the function are selected by a multi-objective genetic algorithm, using propellant and duration of a given maneuver as objectives to minimize. Some numerical examples are presented, showing that a variable-performance maneuver allows for discovering solutions of compromise between the two regimes of an electrospray propulsion system, and enables a broader exploration of the mission design space.

References

- [1] D. Villegas-Prados, S. Correyero, M. Wijnen, and P. Fajardo, "Indirect Characterization of ATHENA Performance, a Novel Externally Wetted Electrospray Propulsion System," in Space Propulsion Conference 2022, 2022.
- [2] Di Pasquale, G., Sanjurjo Rivo, M., and Pérez Grande, D., "A Novel Variable Specific Impulse Optimization Methodology for Modulable Electric Propulsion Systems," AIAA SCITECH 2023 Forum, Jan 23-27 2023. <https://doi.org/10.2514/6.2023-2646>.
- [3] Petropoulos, A. E., "Refinements to the Q-law for the low-thrust orbit transfers," 15th AAS/AIAA Space Flight Mechanics Conference, Copper Mountain, CO, Jan 23-27, 2005. <https://trs.jpl.nasa.gov/handle/2014/37521>.