

Aerospace Europe Conference 2023

Joint 10th EUCASS – 9th CEAS Conference

Abstract #XXX (to be filled by the organizers)
Preferred Topics: PROPHY / SPEXPLO
Corresponding author: Kohji Tominaga
e-mail of corresponding author: tominaga.kohji@jaxa.jp
Type: Oral
Status of corresponding author: Regular

Title

Estimation of Hard Start Mechanism by Visualization Test of Hypergolic Bipropellant Thruster

Authors

Kohji Tominaga ^{1*}, Yu Daimon ², Go Fujii ³, Taiichi Nagata ⁴, Yoshiki Matsuura ⁵, Yasuhito Kano ⁶, Erika Uchiyama ⁷

* Corresponding author

¹ JAXA Research and Development Directorate, 2-1-1 Sengen Tsukuba, Japan, tominaga.kohji@jaxa.jp

² JAXA Research and Development Directorate, 2-1-1 Sengen Tsukuba, Japan, daimon.yu@jaxa.jp

³ JAXA Human Spaceflight Technology Directorate, 2-1-1 Sengen Tsukuba, Japan, fujii.go@jaxa.jp

⁴ JAXA Research and Development Directorate, 2-1-1 Sengen Tsukuba, Japan, nagata.taiichi@jaxa.jp

⁵ IHI AEROSPACE Co., Ltd., Technology Development Department, 900 Fujiki, Tomioka, Japan, yoshiki-matsuura@iac.ihl.co.jp

⁶ IHI AEROSPACE Co., Ltd., Technology Development Department, 900 Fujiki, Tomioka, Japan, yasuhito-kano@iac.ihl.co.jp

⁷ IHI AEROSPACE Co., Ltd., Technology Development Department, 900 Fujiki, Tomioka, Japan, erika-uchiyama@iac.ihl.co.jp

Abstract

Bipropellant thrusters are important components for spacecraft orbit and attitude control by injecting hot combustion gas at high velocity through a nozzle. The oxidizer/fuel is often a combination of nitrogen tetroxide (NTO)/hydrazine (N₂H₄), which is hypergolic propellants. The ignition process is extremely complex because it is a multi-component gas-liquid multiphase flow and involves condensed phase reactions [1]. In recent years, it has become clear that an oxidizer with high vapor pressure becomes a gas-liquid multiphase injection when the chamber pressure is close to a vacuum, such as at the start of propellant injection. In addition, a hard start is likely to occur when such a condition occurs [2]. Hard start has the potential to destroy the combustion chamber by causing a rapid increase in chamber pressure. However, the exact mechanism is not understood.

The objective of this study is to estimate the hard start mechanism of a hypergolic bipropellant thruster from visualization tests and numerical calculations. Using a visualization chamber, high-speed photography and chamber pressure measurements were performed in a vacuum environment to observe the hard start process. In addition, spray tests were performed using simulated fluid with injector backpressure control to observe propellant injection and impact conditions up to the pre-ignition pressure. In the simultaneous oxidizer/fuel injection test, when the injector backpressure was close to vacuum before the hard start occurred, the oxidizer was in flash boiling injection and the propellants collided differently than nominal. Therefore, a large amount of oxidizer impacted the combustion chamber wall surface. Subsequently, the oxidizer on the wall and the fuel for film cooling reacted and vaporized in a liquid-liquid reaction. Calculation of flame propagation velocity from the visualized images at the time of the hard start suggested that the hard start was an ignition with detonation. Based on these results, a hard start scenario was developed by comparing numerical calculations and test results considering detonation.

References

- [1] Y. Daimon, *et al.*, “Flow Field and Heat Transfer Analysis in a MON/MMH Bipropellant Rocket Engine”, *Int. J. Energetic Mater. Chem. Propuls.*, 16(3), 263, 2017.
- [2] G. Fujii, *et al.*, “Visualization of Hard Start Phenomena in Hypergolic Bipropellant Thrusters”, *Space Propulsion* 2022, SP2022_081, 2022.