

Aerospace Europe Conference 2023

Joint 10th EUCASS – 9th CEAS Conference

Abstract #XXX (to be filled by the organizers)

Preferred Topics: CFDMPS / AEROFLIPHY / STRMAT

Corresponding author: GOSMA Mitchell

e-mail of corresponding author: mgosma2@illinois.edu

Type: **Oral** / Poster

Status of corresponding author: Regular / **Student**

For student corresponding author: student member of one of the following:

3AF / AAAR / AIAE / AIDAA / CzAeS / DGLR / FTF / NVvL / PSAA / RAeS / SVFW / EUROAVIA

Title

A Holistic CFD and DSMC Transport Database for Multiphysics Re-entry and Ablation Modeling

Authors

Mitchell GOSMA ^{1*}, Kelly Stephani ¹

** Corresponding author*

¹ Center for Hypersonics and Entry Systems Studies, Department of Mechanical Science and Engineering, University of Illinois at Urbana-Champaign, Urbana, IL, 61801, mgosma2@illinois.edu, ksteph@illinois.edu

Abstract

Hybrid simulation frameworks combining Computational Fluid Dynamics (CFD) and Direct Simulation Monte Carlo (DSMC) are frequently employed to efficiently perform high-fidelity solutions of environments containing combined continuum/rarified flow. The use of DSMC, a stochastic, particle-based method, is necessary for high-Knudsen flow where continuum-based assumptions governing CFD break down. However, the DSMC methodology is generally very computationally inefficient to model the continuum regime. In a CFD/DSMC hybrid approach, obtaining an accurate, high-fidelity solution hinges on the consistent treatment of transport properties and the used thermochemical models employed within the two solvers. In principle, in regions where CFD and DSMC are both employed, the same gas mixture under the same conditions should have the same properties, regardless of simulation type. Observed differences should be due to non-equilibrium processes, rather than differences in physical models.

While the transport models governing CFD and DSMC simulations are starkly different, they can effectively be linked via their use of reduced Chapman-Enskog collision integrals. In CFD, these integrals are typically stored as fitted polynomial expressions and used to directly compute gas transport properties via mixing rules or the full Chapman-Enskog formulation [1]. In DSMC, they can be used to derive the collision parameters needed for the phenomenological collision cross-section models that govern particle interactions, via a Nelder-Mead optimization scheme [2].

The goal of this work is to provide a unified CFD/DSMC transport database encompassing the vast majority of known gas species encountered during atmospheric entry, on Earth or any other Solar body. This goal is largely possible due to recently performed *ab initio* quantum chemistry calculations [3]. Combined with other high-fidelity literature sources, the planned database will consist of collision integral data for over 200 neutral and ionized species and over 17000 binary collisions. From these collision integrals, Nelder-Mead optimization is used to compute Variable Soft Sphere (VSS) collision model parameters for DSMC, fitted from 300 K to 20000 K. Initial comparisons of transport properties of relevant equilibrium gas mixtures show great agreement between CFD and DSMC-derived results.

References

- [1] R. Gupta, NASA TM 101528 (1989).
- [2] K. A. Stephani, Physics of Fluids, 24, 077101 (2012).
- [3] G. Bellas Chatzigeorgis, Physics of Fluids, 34, 087106 (2022).